# **MORTON SALT**

Material Safety Data Sheet

MSDS 065, Revised March 15, 2002 Emergency Phone Number: 312/807-2000

> Hazard Rating (0=None, 4=Extreme)

Health

• Flammability

Reactivity

1. PRODUCT IDENTIFICATION

Sodium Chloride Common Name: Salt

CAS Number: 7647-14-5 Chemical Formula: NaCl

Product Names:

Chemical Name:

Rust Remover Super Pellens

2. COMPOSITION / INFORMATION ON INGREDIENTS

 Formula
 CAS #
 %

 Sodium Chloride
 NaCl
 7647-14-5
 ≥99

 Citric Acid
 C₀H₀O₂
 77-92-9
 ≤0.5

3. HEALTH HAZARD DATA

Effects of Overexposure:

**Ingestion:** Very large doses can cause vomiting, diarrhea, and

prostration. Oral toxicity rat LD<sub>50</sub>: 3000 mg / kg.

**Skin Contact:** Mild skin irritant.

**Eye Contact:** Moderate irritant.

**Inhalation:** Inhalation of dust may cause mild irritation to mucous membranes,

nose and throat. Symptoms may include coughing, dryness and sore throat.

Acute Systemic Effects: Dehydration and congestion may occur in internal organs. Hypertonic salt solutions

can produce inflammatory reactions in the gastrointestinal tract.

Chronic Systemic Effects: No information found.

4. EMERGENCY AND FIRST AID PROCEDURES

Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes. Call a physician if

irritation persists.

**Skin Contact:** Wash exposed area with soap and water. Get medical advice if irritation develops.

**Inhalation:** Remove to fresh air. Get medical attention for any breathing difficulty.

**Ingestion:** If large amounts were swallowed, get medical advice.

#### 5. FIRE AND EXPLOSION HAZARD DATA

Product is non-combustible; no extinguishing media or special fire-fighting procedures are required. There are no unusual fire or explosion hazards.

### 6. REACTIVITY DATA

Stability: X Stable Unstable

Stable and inert under normal conditions. No hazardous polymerization can occur.

No hazardous decomposition products or conditions.

Materials to Avoid: Will react with strong acids (to generate hydrogen chloride) and strong oxidizing agents

(to generate chlorine gas). For citric acid, avoid metal nitrates, strong bases and oxidizers. Aqueous solutions of citric acid will corrode reactive metals (iron, zinc and aluminum) and their alloys, and may generate hydrogen, which could form explosive

mixtures.

## 7. PHYSICAL DATA

Appearance: White pellets pH: 2 - 3

Odor: None % Non-Volatile: 100

Solubility in Water: 36 g / 100 cc water Boiling Point (760 mm Hg): 1413°C (2575°F)

at 20°C (68°F)

#### 8. SPILL OR LEAK PROCEDURES

Response to Small Spills: Sweep up and containerize for reclamation or disposal. Vacuuming or wet

sweeping may be used to avoid dust dispersal.

Response to Large Spills: Shovel and sweep up; containerize for reclamation or disposal.

Hazards to be Avoided: None.

**Reportable Quantity:** Check your state for requirements.

Waste Classification: Some states have set maximum limits on chlorides in waste effluent.

**Disposal Methods:** Whatever cannot be saved for reclamation may be delivered to an approved

waste disposal facility or if local ordinances allow, can be dissolved in sufficient amounts of water to meet water quality standards, and flushed down a sewer

drain. Ensure compliance with local, state and federal regulations.



#### 9. SPECIAL PROTECTION INFORMATION

Respiratory Protection: For conditions of use where exposure to the dust is apparent, a NIOSH approved

dust/mist respirator may be worn. For emergencies, a self-contained breathing

apparatus may be necessary.

For Hands, Body: If deemed necessary, wear protective gloves and clean body-covering clothing.

For Eyes: If deemed necessary, use chemical safety glasses or goggles. Contact lenses should

not be worn when working with this material. Eye wash fountain or water for

eyewashing should be available.

**Ventilation:** In general, dilution ventilation is a satisfactory health hazard control for this substance.

However, if conditions of use create discomfort to the worker, a local exhaust system.

should be considered.

#### 10. SPECIAL PRECAUTIONS

Transport in dry equipment; store in dry location. Handling procedures should minimize generation of airborne dust. Dust respirator as appropriate where exposure exceeds the 10 mg/m³ ACGIH TLV for nuisance dust.

#### 11. LABELING INFORMATION

**DOT Shipping Name:** Salt (common), **Additional Product Label:** Not applicable

sodium chloride

Warning: None

**DOT Label:** Not applicable

UN No.: Not applicable

#### 12. USER'S RESPONSIBILITY

The responsibility to provide a safe workplace remains with the user. The user should consider the health hazards and safety information contained herein as a guide and should take those precautions required in an individual operation to instruct employees and develop work practice procedures for a safe work environment.

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations. Nothing contained herein is to be construed as a recommendation for use in violation of any patents or of applicable laws or regulations.

